

ARDEX SKM™

Skimcoat Patch and Finishing Underlayment

ARDEX SKM™ can be used over interior concrete, wood, ceramic or quarry tile, cutback and other non-water soluble adhesive residues. ARDEX SKM delivers a permanent, smooth, durable finish prior to the installation of floor coverings. ARDEX SKM hardens quickly, is very easy to apply and dries fast without shrinkage.

Key Features

- **Non-sanded for a true featheredge**
- **Creamy consistency; very easy to apply**
- **Trowels to a smooth, hard surface that can be easily sanded**
- **Install floor coverings in as little as 30 minutes**

Installation

- **Priming:** no priming required
- **Coverage:** 150-200 sq.ft. at a skimcoat
- **Mixing:** 1.5 quarts (1.4L) water per 10lb (5kg) bag or 3 parts powder 1 part water by volume
- **Thickness:** featheredge up to 1/2" (12mm)
- **Pot Life:** 15 minutes
- **Walkable:** 30 minutes
- **Install Floor Coverings:**
 - **Skimcoat:** 30 minutes
 - 1/16" to 1/2": Tile 60-90 mins. Other floor coverings 1 to 2 hours
- **VOC:** 0 g/L

Performance


- **VOC:** 0



SystemOne™

Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training click on ARDEX Academy.

For easy-to use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.



**SUBSTRATE
PREPARATION**



AMERICAS

888-512-7339
+1-724-203-5000

www.ardexamericas.com